

# 東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-40046N-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	43200 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

前面	下面開放
反射面	レンズ (広角)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	580	580	580
10°	575	575	575
20°	556	556	556
30°	509	509	509
40°	399	399	399
50°	107	107	107
60°	8	8	8
70°	5	5	5
80°	3	3	3
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	1	1	1
140°	1	1	1
150°	1	1	1
160°	1	1	1
170°	2	2	2
180°	2	2	2

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0			
室指数		固有照明率 (×0.01)																							
0.60		78	72	66	63	60	58	76	71	66	63	59	58	64	62	58	57	58	57	53	52				
0.80		91	83	80	75	73	70	89	81	79	75	73	70	77	74	72	70	71	69	66	65				
1.00		97	87	87	80	80	76	95	86	85	80	79	75	83	79	77	75	76	74	71	70				
1.25		103	92	94	86	87	81	100	90	92	85	86	81	89	84	84	80	82	79	76	75				
1.50		107	94	98	89	92	85	104	93	96	88	90	85	93	87	88	84	86	83	80	79				
2.00		113	98	106	94	100	91	110	97	103	94	98	91	99	92	95	89	92	88	86	84				
2.50		116	100	110	97	104	94	113	99	107	96	102	93	102	94	98	92	95	91	89	87				
3.00		119	102	113	99	108	96	115	101	110	98	105	96	104	96	101	94	97	93	91	89				
4.00		122	103	117	101	113	99	118	102	113	100	110	98	107	98	104	97	100	95	93	91				
5.00		123	104	119	102	116	101	119	103	116	101	112	100	109	99	106	98	101	96	94	93				
10.00		127	106	124	105	122	104	122	105	120	104	118	103	112	102	111	101	105	99	97	95				

