

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-20036N-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	21600 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

前面	下面開放
反射面	レンズ(中角)

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

備考	
----	--

光度(cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	1092	1092	1092
10°	999	999	999
20°	756	756	756
30°	409	409	409
40°	172	172	172
50°	85	85	85
60°	48	48	48
70°	25	25	25
80°	9	9	9
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	1	1	1
150°	1	1	1
160°	2	2	2
170°	3	3	3
180°	3	3	3

反 射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数		固有照明率(×0.01)																																			
0.60		85	78	75	71	68	66	83	77	74	70	68	66	72	70	67	66	67	65	63	62																
0.80		96	87	86	81	80	77	94	86	85	80	79	77	83	79	78	76	77	75	73	72																
1.00		100	90	91	84	84	80	98	89	89	83	83	80	87	82	82	79	80	78	76	74																
1.25		105	93	95	88	89	84	102	92	94	87	88	83	91	86	86	82	84	81	79	77																
1.50		108	95	99	90	93	86	105	94	97	89	92	86	94	88	89	85	87	84	82	80																
2.00		113	98	106	94	100	91	110	97	103	93	98	90	99	92	95	89	92	88	86	84																
2.50		116	100	109	97	104	94	113	99	107	96	102	93	102	94	98	92	94	90	88	87																
3.00		118	101	112	98	107	96	115	100	109	98	105	95	104	96	101	94	96	92	90	89																
4.00		121	103	117	101	113	99	117	102	113	100	110	98	107	98	104	96	100	95	93	91																
5.00		123	104	119	103	116	101	119	103	116	101	113	100	109	99	107	98	102	97	95	93																
10.00		127	107	125	106	124	105	123	105	121	105	120	104	114	103	112	102	106	100	99	97																

