

東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKR426693N-LS9+F-42100



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	5800 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

前面	バツフル (白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	386	386	386
10°	383	374	380
20°	369	347	357
30°	344	307	321
40°	310	252	275
50°	246	193	221
60°	120	131	152
70°	47	70	61
80°	31	26	29
90°	3	1	2
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
室指数		固有照明率 (×0.01)																							
0.60		65	60	51	48	43	41	63	58	50	48	42	41	49	47	42	41	41	40	36	34				
0.80		78	70	64	60	55	53	75	69	63	59	54	52	61	58	53	52	52	51	47	45				
1.00		85	76	71	66	62	59	82	75	70	65	62	59	67	64	60	58	59	57	53	51				
1.25		92	82	80	73	71	67	90	81	78	72	70	66	75	71	68	65	66	64	60	58				
1.50		97	86	86	78	77	71	94	84	84	77	76	71	80	75	73	70	71	69	65	63				
2.00		105	92	95	85	87	80	102	90	93	84	86	79	88	82	82	78	79	77	73	71				
2.50		110	95	101	89	94	84	106	93	98	88	92	84	93	86	88	82	84	81	77	76				
3.00		113	97	105	92	99	88	109	96	102	91	96	87	97	89	92	86	88	84	81	79				
4.00		117	100	111	96	105	93	113	98	108	95	103	92	101	93	98	90	93	89	86	84				
5.00		120	101	115	98	110	96	116	100	111	97	107	95	104	95	101	93	96	91	89	87				
10.00		125	105	122	103	120	102	121	103	118	102	116	100	110	100	108	98	102	97	95	93				

