

# 東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKR426693N-LS9+F-42120



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	5400 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

前面	バツフル (白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.0 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	467	467	467
10°	435	450	442
20°	369	416	380
30°	306	367	312
40°	261	302	247
50°	215	231	191
60°	107	157	136
70°	54	84	58
80°	26	29	26
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
室指数		固有照明率 (×0.01)																							
0.60		66	61	53	50	45	43	65	60	52	50	44	43	51	49	44	43	43	42	38	36				
0.80		79	72	66	61	57	55	77	70	64	61	56	54	62	60	55	54	54	53	49	47				
1.00		86	77	73	68	64	61	83	76	71	67	63	60	69	65	62	60	60	59	55	53				
1.25		93	83	81	74	72	68	90	81	79	73	71	67	76	72	69	66	67	65	61	59				
1.50		98	86	87	79	78	72	95	85	85	78	77	72	81	76	74	71	72	70	66	64				
2.00		106	92	96	86	88	80	102	91	94	85	86	80	89	83	83	78	80	77	74	72				
2.50		110	95	101	90	94	85	106	94	99	89	92	84	94	87	88	83	85	81	78	76				
3.00		114	97	106	93	99	89	110	96	103	92	97	88	97	89	93	86	89	85	82	80				
4.00		118	100	111	96	106	93	114	99	108	95	103	92	102	93	98	91	93	89	86	84				
5.00		120	102	115	99	110	96	116	100	111	98	107	95	105	95	101	93	96	92	89	87				
10.00		126	105	123	103	120	102	121	104	118	102	116	101	111	100	99	103	97	95	93					

