

東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKR426693N-LS9+F-42122



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	5500 lm

保 守 率	良	0.81
	中	0.77
	否	0.72

前面	プリズム
反射面	塗装(白)

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	470	470	470
10°	464	460	463
20°	438	434	435
30°	380	379	379
40°	275	293	286
50°	166	199	186
60°	97	118	88
70°	56	59	42
80°	28	30	25
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反 射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数		固有照明率 (×0.01)																																			
0.60	69	64	56	53	48	47	68	63	55	53	48	47	54	52	47	46	47	46	42	40																	
0.80	82	74	69	65	61	58	80	73	68	64	60	58	66	63	59	57	58	57	53	51																	
1.00	88	79	76	71	68	64	86	78	75	70	67	64	72	68	65	63	64	62	58	57																	
1.25	95	85	84	77	75	71	93	83	82	76	74	70	79	74	72	69	71	69	65	63																	
1.50	100	88	89	81	81	75	97	87	87	80	80	75	84	78	77	74	75	73	69	67																	
2.00	107	93	98	88	91	83	104	92	96	87	89	82	91	85	86	81	83	80	76	75																	
2.50	112	96	103	91	96	87	108	95	100	90	94	86	95	88	91	85	87	83	80	79																	
3.00	115	98	107	94	101	90	111	97	104	93	99	89	99	91	94	88	90	86	84	82																	
4.00	119	101	113	97	107	94	114	99	109	96	104	93	103	94	99	92	95	90	88	86																	
5.00	121	102	116	99	111	97	117	101	112	98	108	96	105	96	102	94	97	92	90	88																	
10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93																	

