

東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKR426693N-LS9+F-4273V



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	5200 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

前面	ルーバー (銀色)
反射面	塗装 (白)

最大取付間隔	
A-A	1.9 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	297	298	298
10°	312	293	304
20°	340	281	309
30°	400	260	322
40°	404	226	338
50°	371	181	310
60°	188	90	193
70°	6	2	7
80°	1	0	1
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	固有照明率 (×0.01)																							
0.60	63	58	49	47	41	39	61	57	48	46	40	39	47	45	39	39	39	38	34	32				
0.80	77	70	63	59	54	52	75	68	62	59	54	52	60	57	53	51	52	50	46	44				
1.00	85	76	72	67	63	60	82	75	70	66	62	59	68	64	61	58	59	58	53	52				
1.25	93	83	81	74	72	68	91	81	79	74	71	67	76	72	69	66	68	66	61	60				
1.50	99	87	87	79	79	73	96	85	85	78	78	73	82	77	75	72	73	71	67	65				
2.00	107	93	98	87	90	82	104	92	95	86	88	82	91	84	85	80	82	79	76	74				
2.50	111	96	103	91	96	87	108	95	100	90	94	86	95	88	91	85	87	83	80	79				
3.00	115	98	107	94	101	90	111	97	104	93	99	90	99	91	95	88	91	87	84	82				
4.00	119	101	113	98	108	95	115	100	110	97	105	94	103	95	100	92	95	91	88	86				
5.00	121	102	116	100	112	97	117	101	113	99	109	96	106	97	103	95	98	93	91	89				
10.00	126	105	123	104	121	102	121	104	119	103	117	101	111	100	109	99	103	97	96	94				

