

東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKR426693N-LS9+F-4273S C



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	5200 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

前面	バツフル (白色)
反射面	塗装 (白)

最大取付間隔	
A-A	1.7 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	321	321	321
10°	337	310	325
20°	347	293	321
30°	364	267	305
40°	363	227	289
50°	307	179	254
60°	138	123	179
70°	44	66	55
80°	22	20	20
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																							
0.60		63	58	49	46	40	39	61	57	48	46	40	39	47	45	39	38	39	38	33	32				
0.80		76	69	62	58	53	51	74	68	61	57	52	50	59	56	51	50	50	49	45	43				
1.00		84	75	70	65	61	58	81	74	69	64	60	57	66	63	59	57	57	56	51	49				
1.25		92	81	79	72	70	66	89	80	77	71	69	65	74	70	67	64	65	63	59	57				
1.50		97	85	85	77	76	71	94	84	83	76	75	70	79	74	73	69	70	68	64	62				
2.00		105	92	95	85	87	79	102	90	93	84	85	79	88	82	82	78	79	76	73	71				
2.50		110	95	101	89	94	84	106	93	98	88	92	84	93	86	88	82	84	81	77	75				
3.00		113	97	105	92	99	88	109	96	102	91	96	87	97	89	92	86	88	84	81	79				
4.00		118	100	111	96	106	93	113	99	108	95	103	92	102	93	98	90	93	89	86	84				
5.00		120	102	115	99	110	96	116	100	111	97	107	95	104	95	101	93	96	91	89	87				
10.00		125	105	123	103	120	102	121	104	118	102	116	101	111	100	99	102	97	95	93					

