

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDS-30116W KB-LS1

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

光源	名称	
	形名	LED
	光束	2300 lm × 1

効 率	F	0%
	F	100%
	F	100%
	器具 光束	2290 lm

備考	
----	--

前面	
反射面	

0°	1335	25°	765
1°		30°	477
2°		35°	236
3°		40°	95
4°		45°	38
5°	1325	50°	21
6°		55°	15
7°		60°	11
8°		65°	4
9°		70°	1
10°	1261	75°	0
11°		80°	0
12°		85°	0
13°		90°	0
14°			
15°	1132		
16°			
17°			
18°			
19°			
20°	979		

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数	照 明 率 (×0.01)																							
0.60	94	87	86	82	81	79	93	86	85	81	81	78	84	81	80	78	79	78	76	75				
0.80	105	95	97	91	92	89	103	94	96	91	92	88	94	90	91	88	89	87	86	85				
1.00	107	96	100	93	95	90	105	96	99	92	94	90	96	91	92	89	91	89	87	86				
1.25	110	98	103	94	98	92	108	97	101	94	97	91	99	93	95	91	93	90	88	87				
1.50	113	99	106	96	101	94	110	99	104	96	100	93	101	94	97	92	95	92	90	89				
2.00	117	101	110	99	106	96	114	100	108	98	104	96	104	97	100	95	97	94	92	91				
2.50	119	103	113	100	109	98	115	102	111	99	107	98	106	98	103	96	99	95	94	92				
3.00	121	103	116	101	112	100	117	102	113	100	109	99	107	99	105	97	101	96	95	93				
4.00	123	105	119	103	116	102	119	104	116	102	113	101	110	100	108	99	103	98	97	95				
5.00	125	105	121	104	119	103	121	104	118	103	115	102	111	101	109	101	104	99	98	96				
10.00	128	107	127	107	125	106	124	106	122	106	121	105	115	104	114	103	108	102	101	99				

