

# 東芝照明器具配光データシート

名称	LEDシーリングライト
形名	LEDH82380-LC



効率	F	11%
	F	89%
	F	100%
	器具光束	5500 lm

保守率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	271	271	271
10°	268	268	268
20°	258	258	258
30°	240	239	240
40°	213	213	213
50°	178	178	178
60°	137	137	137
70°	94	94	94
80°	56	56	56
90°	30	30	30
100°	17	17	17
110°	15	15	15
120°	16	16	16
130°	17	17	17
140°	17	17	17
150°	17	17	17
160°	17	17	17
170°	19	19	19
180°	19	19	19

反射率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	固有照明率 (×0.01)																							
0.60	59	54	45	42	36	35	57	52	43	41	35	34	41	39	34	33	32	32	27	25				
0.80	71	64	56	53	47	45	68	62	54	51	46	44	51	49	44	42	42	41	36	33				
1.00	78	70	63	59	54	51	74	67	61	57	52	50	57	54	50	48	48	46	41	38				
1.25	85	76	72	66	62	58	81	73	69	64	60	57	65	61	57	55	54	52	47	44				
1.50	90	80	77	70	68	63	86	77	75	68	66	62	69	65	62	59	59	57	52	49				
2.00	99	86	87	78	78	71	94	83	84	76	76	70	78	72	71	67	67	64	59	56				
2.50	103	89	93	82	85	76	98	86	89	80	82	75	82	76	77	72	72	69	64	61				
3.00	107	92	98	86	90	80	102	89	94	84	87	79	86	79	81	75	75	72	68	64				
4.00	112	95	104	90	98	86	106	92	100	88	94	84	91	84	87	80	81	77	73	69				
5.00	115	97	108	93	102	89	109	94	103	91	98	87	95	86	91	83	84	80	76	72				
10.00	121	101	117	99	114	97	115	99	112	96	109	94	102	92	99	90	91	86	83	79				

