


東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH80379W-LD



効率	F	9 %
	F	91 %
	F	100 %
	器具光束	3200 lm

保守率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	278	278	278
10°	274	274	274
20°	263	263	263
30°	243	243	243
40°	215	215	216
50°	180	180	181
60°	140	140	141
70°	97	98	99
80°	57	59	59
90°	29	30	30
100°	16	17	17
110°	13	13	13
120°	13	13	13
130°	12	12	13
140°	13	13	13
150°	12	12	12
160°	12	12	12
170°	13	12	12
180°	13	13	13

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	固有照明率 (×0.01)																							
0.60	59	54	45	42	36	35	57	53	44	42	35	34	41	40	34	33	33	32	28	25				
0.80	71	64	56	53	47	45	68	62	55	52	46	44	52	49	44	43	42	41	36	34				
1.00	78	70	64	59	54	51	75	68	62	58	53	50	58	55	50	48	48	47	42	39				
1.25	86	76	72	66	62	58	82	74	69	64	60	57	65	61	57	55	55	53	48	45				
1.50	91	80	78	70	68	63	87	77	75	69	66	62	70	66	63	60	59	58	53	49				
2.00	99	86	87	78	78	72	94	84	84	76	76	70	78	73	72	68	68	65	60	57				
2.50	104	89	93	83	85	77	99	87	90	81	82	75	83	77	77	72	73	70	65	62				
3.00	107	92	98	86	90	81	102	90	94	84	87	79	87	80	82	76	76	73	69	65				
4.00	112	95	105	90	98	86	107	93	100	88	94	84	92	84	88	81	82	78	74	70				
5.00	115	97	109	93	103	89	110	95	104	91	99	88	96	87	92	84	85	81	77	74				
10.00	121	101	118	99	114	97	116	99	112	97	109	95	103	93	100	91	93	88	85	81				

