

# 東芝照明器具配光データシート

|    |                   |
|----|-------------------|
| 名称 | 東芝LED照明器具         |
| 形名 | LEKD1563115WV-LD9 |



|    |      |        |
|----|------|--------|
| 効率 | F    | 0 %    |
|    | F    | 100 %  |
|    | F    | 100 %  |
|    | 器具光束 | 990 lm |

|     |   |      |
|-----|---|------|
| 保守率 | 良 | 0.81 |
|     | 中 | 0.77 |
|     | 否 | 0.68 |

|     |         |
|-----|---------|
| 前面  | 下面開放    |
| 反射面 | 銀色鏡面仕上げ |

|        |        |
|--------|--------|
| 最大取付間隔 |        |
| A-A    | 0.67 H |
| B-B    | 0.67 H |

備考

| 光度 (cd/1000lm)           |  | A-A  | B-B | C-C |
|--------------------------|--|------|-----|-----|
| $\theta \backslash \phi$ |  |      |     |     |
| 0°                       |  | 2010 |     |     |
| 10°                      |  | 1841 |     |     |
| 20°                      |  | 1002 |     |     |
| 30°                      |  | 358  |     |     |
| 40°                      |  | 43   |     |     |
| 50°                      |  | 0    |     |     |
| 60°                      |  | 0    |     |     |
| 70°                      |  | 0    |     |     |
| 80°                      |  | 0    |     |     |
| 90°                      |  | 0    |     |     |
| 100°                     |  | 0    |     |     |
| 110°                     |  | 0    |     |     |
| 120°                     |  | 0    |     |     |
| 130°                     |  | 0    |     |     |
| 140°                     |  | 0    |     |     |
| 150°                     |  | 0    |     |     |
| 160°                     |  | 0    |     |     |
| 170°                     |  | 0    |     |     |
| 180°                     |  | 0    |     |     |

| 反射率 (%) | 天井            |     |     | 70  |     |     | 50  |     |     | 30  |     |     | 20  |     |     | 0   |     |     |     |     |
|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|         | 壁             | 70  | 50  | 30  | 70  | 50  | 30  | 70  | 50  | 30  | 70  | 50  | 30  | 70  | 50  | 30  | 70  | 50  | 30  |     |
| 床       | 30            | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  |     |
| 室指数     | 固有照明率 (×0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 0.60    | 102           | 94  | 95  | 90  | 90  | 88  | 100 | 93  | 94  | 90  | 90  | 88  | 93  | 89  | 89  | 87  | 89  | 87  | 86  | 85  |
| 0.80    | 111           | 101 | 105 | 98  | 101 | 96  | 109 | 100 | 104 | 98  | 100 | 96  | 102 | 97  | 99  | 96  | 98  | 95  | 94  | 94  |
| 1.00    | 112           | 101 | 106 | 98  | 101 | 96  | 110 | 100 | 105 | 98  | 101 | 96  | 102 | 97  | 99  | 95  | 97  | 95  | 94  | 93  |
| 1.25    | 114           | 101 | 107 | 98  | 103 | 96  | 112 | 100 | 106 | 98  | 102 | 96  | 103 | 97  | 100 | 95  | 98  | 95  | 93  | 92  |
| 1.50    | 116           | 102 | 110 | 100 | 105 | 98  | 113 | 101 | 108 | 99  | 104 | 97  | 104 | 98  | 101 | 96  | 99  | 96  | 94  | 93  |
| 2.00    | 119           | 103 | 113 | 101 | 108 | 99  | 115 | 102 | 111 | 100 | 107 | 98  | 106 | 99  | 103 | 97  | 100 | 96  | 95  | 94  |
| 2.50    | 120           | 104 | 115 | 102 | 111 | 100 | 117 | 103 | 113 | 101 | 109 | 100 | 108 | 100 | 105 | 98  | 101 | 97  | 96  | 95  |
| 3.00    | 122           | 105 | 117 | 103 | 114 | 101 | 118 | 104 | 115 | 102 | 111 | 101 | 109 | 100 | 107 | 99  | 102 | 98  | 97  | 95  |
| 4.00    | 124           | 106 | 121 | 105 | 118 | 103 | 121 | 105 | 118 | 104 | 115 | 103 | 111 | 102 | 109 | 101 | 105 | 100 | 98  | 97  |
| 5.00    | 126           | 107 | 123 | 106 | 120 | 105 | 122 | 106 | 120 | 105 | 117 | 104 | 113 | 103 | 111 | 102 | 106 | 101 | 100 | 98  |
| 10.00   | 130           | 108 | 128 | 108 | 127 | 108 | 125 | 107 | 124 | 107 | 123 | 107 | 117 | 105 | 116 | 105 | 110 | 103 | 103 | 101 |

