

東芝照明器具配光データシート

名称	LEDシーリングライト
形名	LEDH81480-LC



効 率	F	9 %
	F	91 %
	F	100 %
	器具 光束	4300 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	267	267	267
10°	265	265	265
20°	257	257	257
30°	240	240	240
40°	215	215	215
50°	182	182	182
60°	143	143	142
70°	99	99	99
80°	60	60	60
90°	31	31	31
100°	17	17	17
110°	13	13	13
120°	13	13	13
130°	13	13	13
140°	12	12	12
150°	11	11	11
160°	10	10	10
170°	10	10	10
180°	11	11	11

反射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																							
0.60		59	54	44	42	36	34	56	52	43	41	35	34	41	39	34	33	32	32	27	25				
0.80		70	64	56	52	46	44	68	62	54	51	45	44	51	49	43	42	42	41	36	33				
1.00		78	70	63	59	53	51	74	67	61	57	52	50	58	55	50	48	48	46	41	39				
1.25		85	76	71	65	62	58	82	73	69	64	60	57	65	61	57	55	54	53	48	45				
1.50		90	80	77	70	67	63	86	77	75	68	66	62	70	65	62	59	59	57	52	49				
2.00		99	86	87	78	78	71	94	83	84	76	76	70	78	72	71	67	67	65	60	57				
2.50		103	89	93	82	85	76	99	87	89	80	82	75	83	77	77	72	72	69	65	61				
3.00		107	92	98	86	90	80	102	89	94	84	87	79	87	80	81	76	76	73	68	65				
4.00		112	95	104	90	98	86	107	93	100	88	94	84	92	84	87	81	81	78	74	70				
5.00		115	97	108	93	102	89	109	95	104	91	98	87	95	87	91	84	85	81	77	73				
10.00		121	101	117	99	114	97	115	99	112	97	109	95	103	93	100	91	92	87	84	81				

