

東芝照明器具配光データシート

名称	LEDシーリングライト
形名	LEDH81475-LC



効 率	F	6 %
	F	94 %
	F	100 %
	器具 光束	4000 lm

保 守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	281	281	281
10°	277	277	277
20°	267	267	267
30°	249	249	249
40°	223	223	223
50°	189	189	189
60°	147	147	147
70°	103	103	103
80°	61	61	61
90°	29	29	29
100°	13	13	13
110°	7	7	7
120°	5	5	5
130°	6	6	6
140°	7	7	7
150°	8	8	8
160°	8	8	8
170°	9	9	9
180°	10	10	10

反 射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数		固有照明率 (×0.01)																																			
0.60	59	55	45	42	36	35	57	53	44	42	35	34	42	40	34	33	33	33	28	26																	
0.80	71	65	56	53	47	45	68	63	55	52	46	44	52	50	44	43	43	42	37	35																	
1.00	78	70	64	59	54	51	75	68	62	58	53	50	59	56	51	49	49	48	43	40																	
1.25	86	76	72	66	62	58	82	74	70	65	61	57	66	62	58	56	56	54	49	46																	
1.50	91	80	78	71	68	63	87	78	75	69	67	62	71	66	63	60	61	59	54	51																	
2.00	99	86	88	78	79	72	95	84	85	77	77	71	79	74	73	69	69	66	62	59																	
2.50	104	90	94	83	85	77	100	88	91	81	83	76	84	78	78	73	74	71	67	64																	
3.00	108	93	99	86	91	81	103	90	95	85	88	80	88	81	83	77	78	75	71	68																	
4.00	113	96	105	91	98	86	108	94	101	89	95	85	94	86	89	82	84	80	76	73																	
5.00	116	98	109	94	103	90	111	96	105	92	100	88	97	88	93	85	87	83	79	76																	
10.00	122	102	118	100	115	97	117	100	113	98	110	96	104	94	102	93	95	90	87	84																	

