

東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEDD-21111ML



効率	F	0 %
	F	100 %
	F	100 %
	器具光束	1250 lm

保守率	良	0.76
	中	0.72
	否	0.64

前面	カバー (フロスト)
反射面	白色

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

$\theta \setminus \phi$	A-A	B-B	C-C
0°	461		
10°	455		
20°	434		
30°	390		
40°	311		
50°	208		
60°	97		
70°	32		
80°	6		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	固有照明率 (×0.01)																							
0.60	70	64	57	54	49	47	68	63	56	53	49	47	54	52	48	47	47	46	42	41				
0.80	83	75	70	66	62	59	81	74	69	65	61	59	67	64	60	59	59	58	54	53				
1.00	89	80	77	72	69	66	87	79	76	71	68	65	74	70	67	65	66	64	60	58				
1.25	97	86	85	78	77	73	94	85	84	78	76	72	81	76	74	71	73	70	67	65				
1.50	101	89	91	82	83	77	98	88	89	82	82	77	85	80	79	76	77	75	71	70				
2.00	109	95	100	89	93	85	105	93	97	88	91	84	93	86	88	83	85	82	79	77				
2.50	113	97	105	93	99	89	109	96	102	92	96	88	97	90	93	87	89	85	83	81				
3.00	116	99	109	95	103	92	112	98	106	94	101	91	100	92	96	90	92	88	86	84				
4.00	119	102	114	99	109	96	115	100	110	97	106	95	104	95	101	93	96	92	89	88				
5.00	122	103	117	100	113	98	117	102	113	99	110	97	107	97	104	95	99	94	92	90				
10.00	126	105	123	104	121	103	122	104	119	103	117	102	112	101	110	100	104	98	96	94				

