

東芝照明器具配光データシート

名称	LEDダウンライト
形名	LEDD87045LWLS



効 率	F ◡	0 %
	F ◒	100 %
	F ○	100 %
	器具 光束	690 lm

保 守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	358		
10°	351		
20°	331		
30°	302		
40°	262		
50°	214		
60°	159		
70°	96		
80°	18		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数		固有照明率 (×0.01)																																			
0.60	63	58	49	46	40	39	61	57	48	46	40	39	47	45	39	38	39	38	34	32																	
0.80	76	69	61	58	52	50	73	67	60	57	52	50	58	56	51	49	50	49	44	42																	
1.00	83	74	69	64	60	57	80	73	68	63	59	56	65	62	58	56	56	55	50	48																	
1.25	91	81	78	71	68	64	88	79	76	70	67	64	73	69	65	63	64	62	57	55																	
1.50	96	84	84	76	75	69	93	83	82	75	73	69	78	73	71	68	69	67	62	60																	
2.00	104	91	94	84	85	78	101	89	91	83	84	77	87	81	81	76	78	75	71	69																	
2.50	109	94	100	88	92	83	105	92	97	87	90	82	92	85	86	81	83	79	76	74																	
3.00	112	96	104	91	97	87	108	95	101	90	95	86	96	88	91	84	87	83	80	78																	
4.00	117	99	110	95	105	92	113	98	107	94	102	91	101	92	97	89	92	88	85	83																	
5.00	120	101	114	98	109	95	115	100	110	97	106	94	104	95	100	92	95	91	88	86																	
10.00	125	105	122	103	119	101	121	103	118	102	116	100	110	100	108	98	102	97	95	93																	

