

東芝照明器具配光データシート

名称	LEDダウンライト
形名	LEDD87042WWWLS



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	550 lm

保 守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

θ	ϕ	光度 (cd/1000lm)		
		A-A	B-B	C-C
0°		365		
10°		357		
20°		337		
30°		307		
40°		266		
50°		216		
60°		159		
70°		93		
80°		14		
90°		0		
100°		0		
110°		0		
120°		0		
130°		0		
140°		0		
150°		0		
160°		0		
170°		0		
180°		0		

反 射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	64	58	49	47	41	40	62	57	49	46	41	39	47	45	40	39	39	38	34	32																	
0.80	76	69	62	58	53	51	74	68	61	58	52	51	59	56	51	50	50	49	45	43																	
1.00	83	75	70	65	61	57	81	73	68	64	60	57	66	62	58	56	57	56	51	49																	
1.25	91	81	78	72	69	65	88	80	77	71	68	64	74	69	66	63	64	63	58	56																	
1.50	96	85	84	77	75	70	93	83	82	76	74	70	79	74	72	68	70	67	63	61																	
2.00	105	91	94	84	86	79	101	90	92	83	85	78	87	81	81	77	78	76	72	70																	
2.50	109	94	100	89	93	84	106	93	98	88	91	83	92	85	87	82	84	80	77	75																	
3.00	113	97	105	92	98	88	109	95	102	91	96	87	96	89	91	85	88	84	81	79																	
4.00	117	100	111	96	105	93	113	98	108	95	103	92	101	93	97	90	93	88	86	84																	
5.00	120	102	115	98	110	96	116	100	111	97	107	95	104	95	101	93	96	91	89	87																	
10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93																	

