

# 東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-16001N-LD9D

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	16400 lm

保守率	良	0.88
	中	0.86
	否	0.82

前面	カバー (乳白)
反射面	白色

最大取付間隔	
A-A	1.1 H
B-B	1.1 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	491		
10°	481		
20°	446		
30°	376		
40°	282		
50°	186		
60°	108		
70°	52		
80°	10		
90°	2		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	70	64	57	54	49	47	68	63	56	53	49	47	54	52	48	47	47	46	42	41																	
0.80	82	75	70	65	62	59	80	73	69	65	61	59	67	64	60	58	59	57	54	52																	
1.00	89	80	77	71	68	65	86	78	75	70	68	65	73	69	66	64	65	63	59	58																	
1.25	96	85	85	77	76	72	93	84	83	77	75	71	80	75	73	70	71	69	66	64																	
1.50	101	89	90	82	82	76	98	87	88	81	81	76	84	79	78	75	76	74	70	68																	
2.00	108	94	99	88	92	84	105	93	96	87	90	83	92	85	87	82	84	80	77	75																	
2.50	112	97	104	92	97	88	108	95	101	91	95	87	96	89	91	86	88	84	81	79																	
3.00	115	99	108	95	102	91	111	97	105	93	100	90	99	91	95	89	91	87	84	83																	
4.00	119	101	113	98	108	95	115	100	110	97	105	94	104	95	100	93	95	91	88	87																	
5.00	121	103	116	100	112	97	117	101	113	99	109	97	106	97	103	95	98	93	91	89																	
10.00	126	105	123	104	121	103	121	104	119	103	117	102	111	101	100	103	98	96	94	94																	

