

東芝照明器具配光データシート

| | |
|----|-----------------|
| 名称 | LED高天井用照明器具 |
| 形名 | LEDJ43002N-LD9D |

| | |
|--|--|
| | |
|--|--|

| | | |
|--------|------|----------|
| 効 率 | F | 0 % |
| | F | 100 % |
| | F | 100 % |
| | 器具光束 | 40200 lm |

| | | |
|-----|---|------|
| 保守率 | 良 | 0.88 |
| | 中 | 0.86 |
| | 否 | 0.82 |

| | |
|-----|----------|
| 前面 | カバー (乳白) |
| 反射面 | 鏡面処理 |

| | |
|--------|-------|
| 最大取付間隔 | |
| A-A | 0.9 H |
| B-B | 0.9 H |

| | |
|----|--|
| 備考 | |
|----|--|

| 光度 (cd/1000lm) | | | |
|-------------------------|-----|-----|-----|
| $\theta \setminus \phi$ | A-A | B-B | C-C |
| 0° | 740 | | |
| 10° | 691 | | |
| 20° | 564 | | |
| 30° | 402 | | |
| 40° | 255 | | |
| 50° | 146 | | |
| 60° | 75 | | |
| 70° | 33 | | |
| 80° | 9 | | |
| 90° | 2 | | |
| 100° | 0 | | |
| 110° | 0 | | |
| 120° | 0 | | |
| 130° | 0 | | |
| 140° | 0 | | |
| 150° | 0 | | |
| 160° | 0 | | |
| 170° | 0 | | |
| 180° | 0 | | |

| 反射率 (%) | 天井 | 80 | | | | | | 70 | | | | | | 50 | | | | | | 30 | | | | | | 20 | | | | | | 0 | | | | | |
|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|--|--|--|--|
| | 壁 | 70 | | 50 | | 30 | | 70 | | 50 | | 30 | | 50 | | 30 | | 50 | | 30 | | 30 | | 10 | | 0 | | 30 | | 10 | | 0 | | | | | |
| | 床 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | | | | |
| 室指数 | 固有照明率 (×0.01) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.60 | 76 | 70 | 64 | 61 | 57 | 55 | 74 | 69 | 64 | 61 | 57 | 55 | 62 | 60 | 56 | 55 | 55 | 54 | 51 | 50 | | | | | | | | | | | | | | | | | |
| 0.80 | 88 | 80 | 77 | 72 | 70 | 67 | 86 | 79 | 76 | 72 | 69 | 67 | 74 | 71 | 68 | 66 | 67 | 65 | 62 | 61 | | | | | | | | | | | | | | | | | |
| 1.00 | 94 | 84 | 83 | 77 | 76 | 72 | 92 | 83 | 82 | 76 | 75 | 71 | 79 | 75 | 73 | 71 | 72 | 70 | 67 | 65 | | | | | | | | | | | | | | | | | |
| 1.25 | 100 | 89 | 90 | 82 | 82 | 77 | 97 | 88 | 88 | 81 | 81 | 77 | 85 | 80 | 79 | 76 | 77 | 75 | 72 | 70 | | | | | | | | | | | | | | | | | |
| 1.50 | 104 | 92 | 94 | 86 | 87 | 81 | 101 | 90 | 92 | 85 | 86 | 80 | 89 | 83 | 83 | 80 | 81 | 79 | 75 | 74 | | | | | | | | | | | | | | | | | |
| 2.00 | 111 | 96 | 102 | 91 | 96 | 87 | 107 | 95 | 100 | 90 | 94 | 87 | 95 | 89 | 91 | 85 | 87 | 84 | 81 | 80 | | | | | | | | | | | | | | | | | |
| 2.50 | 114 | 98 | 107 | 94 | 101 | 91 | 110 | 97 | 104 | 93 | 99 | 90 | 99 | 91 | 95 | 89 | 91 | 87 | 85 | 83 | | | | | | | | | | | | | | | | | |
| 3.00 | 117 | 100 | 110 | 97 | 105 | 93 | 113 | 99 | 107 | 96 | 102 | 93 | 102 | 94 | 98 | 91 | 94 | 90 | 87 | 86 | | | | | | | | | | | | | | | | | |
| 4.00 | 120 | 102 | 115 | 99 | 110 | 97 | 116 | 101 | 112 | 98 | 107 | 96 | 105 | 96 | 102 | 94 | 97 | 93 | 91 | 89 | | | | | | | | | | | | | | | | | |
| 5.00 | 122 | 103 | 118 | 101 | 114 | 99 | 118 | 102 | 114 | 100 | 111 | 98 | 108 | 98 | 105 | 96 | 100 | 95 | 93 | 91 | | | | | | | | | | | | | | | | | |
| 10.00 | 127 | 106 | 124 | 105 | 122 | 104 | 122 | 105 | 120 | 104 | 118 | 103 | 112 | 101 | 111 | 101 | 105 | 99 | 97 | 95 | | | | | | | | | | | | | | | | | |

