

東芝照明器具配光データシート

名称	東芝LED器具
形名	LSS10MP/RP-4-46



効 率	F	5 %
	F	95 %
	F	100 %
	器具 光束	5000 lm

保 守 率	良	0.88
	中	0.86
	否	0.81

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

東芝形名: LEKTW423524SN-LS9

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	302	303	303
10°	299	298	298
20°	286	281	283
30°	265	255	259
40°	235	220	227
50°	200	179	188
60°	160	132	144
70°	120	81	100
80°	83	30	59
90°	52	1	31
100°	31	1	16
110°	20	1	11
120°	14	1	1
130°	1	1	1
140°	1	1	1
150°	1	1	1
160°	1	1	1
170°	1	1	1
180°	1	1	1

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																							
0.60		60	55	46	43	37	36	58	54	45	43	36	35	43	41	35	35	34	34	29	27				
0.80		72	65	57	54	48	46	69	64	56	53	47	45	53	51	46	44	44	43	38	36				
1.00		79	71	65	60	55	52	76	69	63	59	54	52	60	57	52	50	50	49	44	42				
1.25		87	77	73	67	63	59	83	75	71	66	62	59	67	63	59	57	57	55	51	48				
1.50		92	81	79	72	69	64	88	79	77	70	68	63	72	68	65	62	62	60	55	53				
2.00		100	87	89	79	80	73	96	85	86	78	78	72	81	75	74	70	70	68	63	60				
2.50		105	91	95	84	86	78	101	88	91	82	84	77	86	79	79	74	75	72	68	65				
3.00		109	93	99	87	92	82	104	91	96	85	89	81	89	82	84	78	79	76	72	69				
4.00		113	96	106	92	99	87	109	94	102	90	96	86	95	87	90	83	85	81	77	74				
5.00		116	98	110	94	104	90	111	96	106	93	100	89	98	89	94	86	88	84	80	77				
10.00		123	102	119	100	115	98	117	101	114	98	111	96	105	95	103	93	96	91	88	85				

