

# 東芝照明器具配光データシート

名称	LEDダウンライト
形名	LEDD20035NLD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	17900 lm

保 守 率	良	0.83
	中	0.81
	否	0.77

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	463		
10°	454		
20°	428		
30°	384		
40°	320		
50°	216		
60°	95		
70°	22		
80°	12		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	固有照明率 (×0.01)																							
0.60	70	64	57	54	49	47	68	63	56	53	48	47	54	52	48	47	47	46	42	41				
0.80	83	75	70	66	62	59	81	74	69	65	61	59	67	64	60	59	59	58	54	52				
1.00	89	80	77	72	69	66	87	79	76	71	68	65	74	70	67	65	66	64	60	58				
1.25	97	86	86	78	77	73	94	85	84	78	76	72	81	76	74	71	73	70	67	65				
1.50	101	89	91	83	83	77	98	88	89	82	82	77	85	80	80	76	77	75	71	70				
2.00	109	95	100	89	93	85	106	93	98	88	91	84	93	87	88	83	85	82	79	77				
2.50	113	97	105	93	99	89	109	96	102	92	97	88	97	90	93	87	89	86	83	81				
3.00	116	99	109	95	103	92	112	98	106	94	101	91	100	92	96	90	92	88	86	84				
4.00	120	102	114	99	109	96	115	100	111	98	106	95	104	96	101	93	96	92	89	88				
5.00	122	103	117	100	113	98	117	102	113	99	110	97	107	97	104	95	99	94	92	90				
10.00	126	106	124	104	121	103	122	104	119	103	117	102	112	101	110	100	104	98	96	94				

