

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-16006N-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	16100 lm

保守率	良	0.88
	中	0.86
	否	0.82

前面	カバー (透明)
反射面	アルミ蒸着処理

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	717		
10°	773		
20°	664		
30°	453		
40°	272		
50°	139		
60°	28		
70°	4		
80°	1		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	81	74	70	66	63	61	79	73	69	66	63	61	68	65	62	61	62	60	57	56																	
0.80	93	85	83	78	76	73	91	84	82	77	76	73	80	76	75	72	74	72	69	68																	
1.00	98	88	89	82	82	78	96	87	87	82	81	77	85	80	80	77	78	76	73	72																	
1.25	104	92	95	87	88	83	101	91	93	86	87	82	90	85	85	81	83	81	78	77																	
1.50	108	95	99	90	93	86	105	94	97	89	91	86	94	88	89	85	87	84	81	80																	
2.00	114	99	106	95	100	92	110	98	104	94	99	91	99	92	95	90	92	89	86	85																	
2.50	117	101	110	97	105	94	113	99	107	96	103	94	103	95	99	93	95	91	89	88																	
3.00	119	102	113	99	108	97	115	101	110	98	106	96	105	96	101	94	97	93	91	90																	
4.00	122	104	117	101	113	99	118	103	114	101	110	99	108	99	105	97	100	96	94	92																	
5.00	124	105	120	103	116	101	120	103	116	102	113	100	110	100	107	99	102	97	95	94																	
10.00	127	107	125	106	123	105	123	105	121	105	119	104	113	102	112	102	106	100	99	97																	

