

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ34006DN-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	30600 lm

保守率	良	0.88
	中	0.86
	否	0.82

前面	カバー (乳白)
反射面	アルミ蒸着処理

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	732		
10°	711		
20°	602		
30°	428		
40°	260		
50°	135		
60°	67		
70°	19		
80°	6		
90°	1		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	78	72	66	63	59	58	76	71	66	63	59	57	64	62	58	57	58	57	53	52																	
0.80	90	82	79	74	72	69	88	81	78	74	72	69	76	73	70	68	69	68	65	63																	
1.00	95	86	85	79	78	74	93	85	84	78	77	74	81	77	76	73	74	72	69	68																	
1.25	101	90	91	84	84	79	99	89	90	83	83	79	87	82	81	78	79	77	74	72																	
1.50	105	93	96	87	89	83	103	92	94	86	88	82	91	85	85	81	83	80	78	76																	
2.00	112	97	104	93	97	89	108	96	101	92	96	88	97	90	92	87	89	86	83	82																	
2.50	115	99	108	95	102	92	111	98	105	94	100	91	100	93	96	90	93	89	86	85																	
3.00	118	101	111	97	106	95	114	100	108	96	104	94	103	95	99	92	95	91	89	87																	
4.00	121	103	116	100	111	98	117	102	112	99	109	97	106	97	103	95	99	94	92	90																	
5.00	123	104	119	102	115	100	119	103	115	101	112	99	108	99	106	97	101	96	94	92																	
10.00	127	106	125	105	122	104	122	105	120	104	118	103	113	102	111	101	105	99	98	96																	

