

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-10507N-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	11400 lm

保守率	良	0.83
	中	0.81
	否	0.77

前面	カバー (透明)
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	342		
10°	337		
20°	322		
30°	298		
40°	264		
50°	212		
60°	154		
70°	90		
80°	34		
90°	5		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	63	58	48	46	40	39	61	56	48	45	39	38	46	44	39	38	38	37	33	31																	
0.80	75	68	61	57	52	50	73	67	60	56	51	49	58	55	50	49	49	48	43	41																	
1.00	82	74	69	64	59	56	80	72	67	63	58	56	65	61	57	55	56	54	49	47																	
1.25	90	80	77	71	68	63	87	79	75	70	67	63	72	68	65	62	63	61	56	54																	
1.50	95	84	83	75	74	69	92	82	81	74	73	68	77	72	70	67	68	66	61	59																	
2.00	104	90	93	83	85	77	100	89	91	82	83	77	86	80	80	75	77	74	70	68																	
2.50	108	94	99	87	91	82	105	92	96	86	89	81	91	84	85	80	82	79	75	73																	
3.00	112	96	104	91	96	86	108	94	101	90	94	85	95	87	90	84	86	82	79	77																	
4.00	117	99	110	95	104	91	112	98	106	94	101	90	100	92	96	89	91	87	84	82																	
5.00	119	101	114	97	108	94	115	99	110	96	105	93	103	94	100	92	94	90	87	85																	
10.00	125	105	122	103	119	101	120	103	118	102	115	100	110	99	108	98	102	96	94	92																	

