

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-20029N-LD9+LEDX20063GF

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	20500 lm

保守率	良	0.81
	中	0.77
	否	0.72

前面	カバー (乳白)
反射面	

最大取付間隔	
A-A	1.1 H
B-B	1.1 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	460		
10°	449		
20°	414		
30°	354		
40°	272		
50°	186		
60°	118		
70°	64		
80°	23		
90°	0		
100°	0		
110°	0		
120°	0		
130°	1		
140°	1		
150°	2		
160°	2		
170°	2		
180°	3		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	68	62	55	52	47	45	66	61	54	51	46	45	52	50	45	44	45	44	40	38																	
0.80	80	73	67	63	59	56	78	72	66	62	58	56	64	61	57	55	56	55	51	49																	
1.00	87	78	74	69	66	62	85	77	73	68	65	62	70	67	63	61	62	60	56	55																	
1.25	94	84	82	75	74	69	91	82	81	75	73	69	77	73	71	68	69	67	63	61																	
1.50	99	87	88	80	79	74	96	86	86	79	78	73	82	77	76	72	73	71	67	65																	
2.00	107	93	97	87	89	81	103	91	94	86	88	81	90	84	84	80	81	78	75	73																	
2.50	111	96	102	90	95	86	107	94	99	89	93	85	94	87	89	84	86	82	79	77																	
3.00	114	98	106	93	100	89	110	96	103	92	98	88	98	90	93	87	89	85	82	80																	
4.00	118	100	112	97	107	94	114	99	109	96	104	93	102	94	99	91	94	89	87	85																	
5.00	121	102	115	99	111	96	116	101	112	98	108	95	105	96	102	94	97	92	89	87																	
10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93																	

