

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-20031N-LD9+LEDX20063GF

--	--

効 率	F	1 %
	F	99 %
	F	100 %
	器具光束	20500 lm

保守率	良	0.81
	中	0.77
	否	0.72

前面	カバー(乳白)
反射面	

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

備考	
----	--

θ \ φ	A-A B-B C-C		
	0°	819	
10°	751		
20°	572		
30°	363		
40°	218		
50°	136		
60°	84		
70°	47		
80°	18		
90°	0		
100°	0		
110°	1		
120°	1		
130°	2		
140°	2		
150°	3		
160°	3		
170°	4		
180°	5		

反射率 (%)	天井		80						70						50						30						20						0																
	壁	床	70		50		30		70		50		30		50		30		50		30		50		30		50		30		50		30		50														
			30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10															
室指数		固有照明率 (×0.01)																																															
0.60	76	70	64	61	57	56	74	69	64	61	57	55	62	60	56	55	55	54	51	50																													
0.80	88	80	76	72	69	66	86	78	75	71	68	66	73	70	67	65	66	65	61	60																													
1.00	93	84	82	76	75	71	91	82	81	75	74	70	78	74	72	70	71	69	65	64																													
1.25	99	88	88	81	81	76	96	87	87	80	80	75	84	79	78	74	76	73	70	68																													
1.50	103	91	93	84	86	80	100	89	91	84	84	79	87	82	82	78	80	77	74	72																													
2.00	109	95	101	90	94	86	106	94	98	89	92	85	94	87	89	84	86	82	79	78																													
2.50	113	98	105	93	99	89	109	96	103	92	97	89	97	90	93	87	89	86	83	81																													
3.00	116	99	109	95	103	92	112	98	106	94	101	91	100	92	96	90	92	88	86	84																													
4.00	119	102	114	99	109	96	115	100	111	98	106	95	104	95	101	93	96	92	89	87																													
5.00	122	103	117	100	113	98	117	102	113	99	110	97	107	97	104	95	99	94	92	90																													
10.00	126	106	124	104	122	103	122	104	120	103	118	102	112	101	110	100	104	98	96	94																													

