

# 東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEKD60981L-LD9



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	5100 lm

保守 率	良	0.77
	中	0.72
	否	0.68

前面	カバー（透明）
反射面	銀色梨地

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

$\theta$	$\phi$	光度 (cd/1000lm)		
		A-A	B-B	C-C
0°		626		
10°		652		
20°		652		
30°		524		
40°		262		
50°		107		
60°		40		
70°		15		
80°		1		
90°		0		
100°		0		
110°		0		
120°		0		
130°		0		
140°		0		
150°		0		
160°		0		
170°		0		
180°		0		

反射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		30		10		0		30		10		0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	80	73	69	65	62	60	78	73	68	65	62	60	67	64	61	60	60	59	56	55																	
0.80	92	84	82	77	75	72	90	83	81	76	75	72	79	75	73	71	72	71	68	67																	
1.00	97	88	87	81	81	77	95	87	86	81	80	76	84	79	78	76	77	75	72	71																	
1.25	103	92	94	86	87	82	101	91	92	85	86	81	89	84	84	80	82	80	77	75																	
1.50	107	94	98	89	92	85	104	93	96	88	90	85	93	87	88	84	86	83	80	79																	
2.00	113	98	105	94	99	91	110	97	103	93	98	90	99	92	94	89	91	88	86	84																	
2.50	116	100	109	97	104	94	113	99	107	96	102	93	102	94	98	92	94	91	88	87																	
3.00	118	102	113	99	108	96	115	100	110	98	105	95	104	96	101	94	97	92	90	89																	
4.00	121	103	117	101	113	99	117	102	113	100	110	98	107	98	104	96	100	95	93	91																	
5.00	123	104	119	102	116	101	119	103	116	101	112	100	109	99	107	98	101	96	95	93																	
10.00	127	106	125	105	123	104	122	105	121	104	119	103	113	102	112	101	105	99	98	96																	

