


# ■ 東芝ランプ 配光データシート

名称	LEDユニットフラット
形名	LDF6L-WGX/C 7/7/2
光束	800 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具光束	800 lm

最大取付間隔	
A-A	0.71 H
B-B	0.71 H

備考  
データは初期の標準値です。

θ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	924		
10°	814		
20°	546		
30°	279		
40°	177		
50°	130		
60°	92		
70°	61		
80°	37		
90°	17		
100°	15		
110°	10		
120°	7		
130°	8		
140°	9		
150°	8		
160°	6		
170°	4		
180°	3		

反射率 (%)	天井		80				70				50				30		20		0		
	壁	床	70	50	30	70	50	30	70	50	30	50	30	30	10	30	10	0			
室指数		照明率 (×0.01)																			
0.60		76	70	64	61	56	55	74	69	63	60	56	54	61	58	55	53	53	52	49	47
0.80		87	79	75	71	67	65	85	78	74	70	67	64	71	68	65	63	63	62	58	56
1.00		93	83	81	75	73	69	90	81	79	74	71	68	76	72	69	67	67	66	62	60
1.25		98	87	87	80	79	74	95	86	85	78	77	73	81	76	75	71	72	70	66	64
1.50		103	90	92	83	84	78	99	88	89	82	82	77	85	79	79	75	76	73	69	67
2.00		109	95	100	89	92	84	105	93	97	87	90	83	91	85	85	81	82	79	75	72
2.50		113	98	104	92	97	88	109	96	101	91	95	87	95	88	90	84	85	82	78	76
3.00		116	100	108	95	102	91	111	97	105	93	99	90	98	90	93	87	88	85	81	78
4.00		120	102	114	98	108	95	115	100	110	97	105	94	102	94	98	91	93	88	85	82
5.00		123	104	117	101	112	98	118	102	113	99	109	96	105	96	102	93	95	91	88	85
10.00		128	107	125	106	122	104	123	105	120	104	118	102	111	100	109	99	102	96	94	91

