

東芝照明器具配光データシート



名 称	東芝白熱灯ダウンライト
形 名	ID-7364NS (W)

光源	名 称	ミニクリプトンランプ
	形 名	KR100/110V6 OWPS35W
	光 束	800 lm × 1

前 面	下面開放
反射面	上部：銀色鏡面、下部 白色塗装

保守率	良	0.81
	中	0.77
	否	0.67

効 率	F 	0 %
	F 	75 %
	F 	75 %
	器具 光束	601 lm



最大取付間隔	
A-A	0.8 H
B-B	0.9 H

備 考	
--------	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	464	464	464
10°	393	419	427
20°	309	343	344
30°	225	264	264
40°	161	183	185
50°	120	129	133
60°	89	96	99
70°	49	52	53
80°	17	17	17
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		49	45	39	37	33	32	48	44	38	37	32	32	37	36	32	31	31	31	28	26
0.80		57	52	47	44	41	39	56	51	46	44	40	39	45	43	39	38	39	38	34	33
1.00		64	58	54	50	48	45	62	57	53	50	47	45	51	49	46	44	45	44	40	39
1.25		69	62	60	55	53	50	67	61	59	54	53	50	56	53	51	49	50	48	45	44
1.50		74	65	65	59	58	54	71	64	63	58	57	54	61	57	56	53	54	52	49	48
2.00		79	69	72	64	66	60	77	68	70	63	64	59	66	62	62	58	60	57	55	53
2.50		83	71	76	67	70	64	80	70	74	66	69	63	70	65	66	62	63	61	58	57
3.00		85	73	79	69	74	66	82	72	77	69	72	66	73	67	69	64	66	63	61	60
4.00		88	75	84	72	79	70	85	74	81	71	77	69	76	70	73	68	70	67	65	63
5.00		90	76	86	74	83	72	87	75	84	73	80	71	79	72	76	70	72	69	67	65
10.00		94	79	92	78	90	77	91	78	89	77	87	76	83	75	82	74	77	73	72	70

