

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FR-21720

光源	名 称	蛍光ランプ
	形 名	FL20SS・EX-N /18-H
	光 束	1470 lm × 1

前 面	バッフル (白)
反射面	塗装 (白)

保守率	良	0.70
	中	0.66
	否	0.61

効 率	F 	0 %
	F 	76 %
	F 	76 %
	器具 光束	1111 lm



最大取付間隔	
A-A	1.4 H
B-B	1.2 H

備 考	
--------	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	282	282	282
10°	279	274	276
20°	271	254	261
30°	259	226	238
40°	234	191	210
50°	181	149	172
60°	106	103	115
70°	47	54	54
80°	15	19	17
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		48	45	38	36	32	31	47	44	37	36	31	30	36	35	31	30	30	30	26	25		
0.80		58	53	48	45	41	39	56	52	47	44	40	39	45	43	40	38	39	38	35	33		
1.00		64	57	53	50	47	44	62	56	52	49	46	44	50	48	45	43	44	43	39	38		
1.25		69	62	60	55	53	50	67	61	59	54	52	49	56	53	51	49	49	48	45	43		
1.50		73	64	64	58	58	54	71	63	63	58	57	53	60	56	55	52	53	52	48	47		
2.00		79	69	72	64	66	60	77	68	70	63	64	59	67	62	62	58	60	58	55	53		
2.50		83	71	76	67	71	64	80	70	74	66	69	63	70	65	66	62	64	61	58	57		
3.00		85	73	79	70	74	66	82	72	77	69	73	66	73	67	69	65	66	64	61	60		
4.00		89	75	84	73	80	70	86	74	81	72	78	69	77	70	74	68	70	67	65	63		
5.00		91	77	87	74	83	72	87	76	84	73	81	71	79	72	76	70	72	69	67	65		
10.00		95	79	92	78	90	77	91	78	89	77	87	76	83	75	82	74	77	73	72	70		

