

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FT-91101

光源	名 称	蛍光ランプ
	形 名	FLR110H・EX-N/A-H
	光束	9220 lm × 1

前 面	下面開放
反射面	塗装（白）

保守率	良	0.74
	中	0.70
	否	0.62

効 率	F 	1 %
	F 	83 %
	F 	84 %
	器具光束	7691 lm



最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ ϕ	A-A	B-B	C-C
0°	220	220	220
10°	218	218	220
20°	218	208	215
30°	213	192	205
40°	203	169	191
50°	187	146	174
60°	159	110	149
70°	128	72	110
80°	72	36	67
90°	15	0	14
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		49	45	36	34	29	28	47	44	35	34	28	27	34	33	28	27	27	26	23	21		
0.80		59	53	46	43	38	36	57	52	45	42	37	36	43	41	36	35	35	34	30	28		
1.00		65	58	52	48	44	41	62	57	51	48	43	41	49	46	42	40	41	39	35	33		
1.25		71	63	59	54	51	48	69	62	58	53	50	47	55	52	48	46	47	45	41	39		
1.50		76	67	64	58	56	52	73	65	63	57	55	51	59	56	53	50	51	49	45	43		
2.00		83	72	73	65	65	59	80	71	71	64	64	59	67	62	61	58	59	56	52	51		
2.50		87	75	78	69	71	64	84	74	76	68	69	63	72	66	66	62	63	61	57	55		
3.00		91	78	83	72	76	68	87	76	80	71	74	67	75	69	70	65	67	64	61	59		
4.00		95	81	88	76	83	73	91	79	85	75	80	72	80	73	76	70	72	69	66	64		
5.00		97	82	92	79	87	76	94	81	89	78	84	75	83	76	79	73	75	71	69	67		
10.00		103	86	100	84	97	82	99	85	96	83	94	81	90	81	88	80	82	78	76	74		

