



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FRX-4402K

保守率	良	0.70
	中	0.66
	否	0.61



光源	名称	蛍光ランプ
	形名	FLR40S・W/M
	光束	3000 lm × 4

効率	F	0%
	F	58%
	F	58%
	器具光束	7015 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

前面	乳白アクリルカバー
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	197	197	197
10°	193	193	193
20°	183	183	183
30°	167	167	167
40°	147	144	146
50°	122	118	120
60°	93	88	92
70°	63	56	61
80°	32	23	30
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80		70		50		30		20		0							
	壁	床	70	50	30	70	50	30	50	30	30	10	10	0						
室指数	照明率 (×0.01)																			
0.60	36	33	28	26	22	22	35	32	27	26	22	22	26	25	22	21	21	21	18	17
0.80	43	39	35	32	29	28	42	38	34	32	29	28	33	31	28	27	28	27	24	23
1.00	47	42	39	36	33	32	46	42	38	36	33	31	37	35	32	31	31	31	28	27
1.25	52	46	44	40	38	36	50	45	43	40	38	36	41	39	37	35	36	35	32	31
1.50	55	48	47	43	42	39	53	47	46	42	41	39	44	41	40	38	39	37	35	33
2.00	60	52	53	48	48	44	58	51	52	47	47	44	49	46	45	43	44	42	40	38
2.50	63	54	57	50	52	47	60	53	55	50	51	47	52	48	49	46	47	45	43	41
3.00	65	55	60	52	55	49	62	55	58	52	54	49	55	50	52	48	49	47	45	44
4.00	68	57	63	55	60	53	65	56	61	54	58	52	58	53	55	51	53	50	48	47
5.00	69	58	66	56	63	54	67	58	64	56	61	54	60	54	57	53	55	52	50	49
10.00	73	61	71	60	69	59	70	60	68	59	67	58	64	58	63	57	59	56	55	53

