



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FT-42305

保守率	良	0.74
	中	0.70
	否	0.61



光源	名称	蛍光ランプ
	形名	FLR40S・W/M
	光束	3000 lm × 2

効率	F	17%
	F	74%
	F	91%
	器具光束	5465 lm

最大取付間隔	
A-A	1.5 H
B-B	1.3 H

備考	
----	--

前面	
反射面	ステンレス

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	177	177	177
10°	176	174	175
20°	175	165	170
30°	173	150	161
40°	170	130	152
50°	162	105	139
60°	151	78	121
70°	149	48	105
80°	124	19	91
90°	85	0	57
100°	77	0	47
110°	65	0	43
120°	62	0	38
130°	50	0	19
140°	24	0	3
150°	2	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	70	50	30	70	50	30	50	30	30	10	0				
室指数	照明率 (×0.01)																			
0.60	50	46	36	35	28	27	47	44	35	33	27	26	32	31	26	25	24	23	19	17
0.80	60	54	46	43	37	35	56	52	44	41	36	34	40	38	33	32	31	30	25	23
1.00	66	59	52	48	43	41	62	57	50	47	41	40	46	43	39	37	36	35	30	27
1.25	73	65	60	55	50	47	69	62	57	53	48	45	52	49	45	43	41	40	35	31
1.50	77	68	65	59	55	51	73	65	62	57	53	50	56	52	49	47	45	44	38	35
2.00	85	74	74	66	65	59	80	71	70	63	62	57	63	59	57	54	52	50	45	41
2.50	89	77	79	70	71	64	84	74	75	67	68	62	68	63	62	58	56	54	49	45
3.00	93	80	84	73	76	68	87	77	79	71	72	66	71	66	66	61	60	57	53	48
4.00	98	83	90	78	83	73	92	80	85	75	79	71	76	70	72	66	65	62	57	53
5.00	100	85	94	80	88	76	95	82	89	78	83	74	79	72	75	69	68	65	60	56
10.00	107	89	103	87	99	84	101	86	97	84	94	82	87	78	84	76	76	72	68	63

