



東芝照明器具配光データシート

名 称		安全増防爆白熱灯器具		良	0.89		θ 			
形 名		BIS104-16CL						中	0.84	ϕ 
保守率		否								
光 源	名称	耐振電球		効 率	F  13 %	最大取付間隔	備考			
	形名	TAI110V100W E						F  53 %	A-A 0.8 H	
	光束	1150 lm × 1						F  66 %	B-B 0.8 H	
前 面		ガード		器具 光束	755 lm					
反射面										

光度 (cd/1000lm)				
$\theta \backslash \phi$	A-A	B-B	C-C	
0°	170			
10°	119			
20°	109			
30°	100			
40°	95			
50°	95			
60°	99			
70°	45			
80°	77			
90°	69			
100°	70			
110°	6			
120°	3			
130°	2			
140°	2			
150°	1			
160°	0			
170°	0			
180°	0			

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		照 明 率 (×0.01)																						
0.60		34	31	24	23	18	18	32	30	23	22	17	17	21	20	16	16	15	15	11	9			
0.80		41	37	30	28	24	23	38	35	29	27	23	22	26	25	21	20	19	19	15	13			
1.00		46	41	36	33	29	27	43	39	34	32	28	26	31	29	25	25	23	23	19	17			
1.25		51	45	41	37	34	31	48	43	39	36	32	30	35	33	30	28	27	26	22	20			
1.50		54	48	45	41	38	35	51	46	42	39	36	34	38	36	33	31	30	29	25	22			
2.00		60	52	51	45	44	40	56	49	48	44	42	39	43	40	38	36	35	33	29	26			
2.50		63	54	55	48	48	44	59	52	52	47	46	42	47	43	42	39	38	36	32	29			
3.00		65	56	58	51	52	46	61	54	55	49	49	45	49	45	45	42	40	39	35	32			
4.00		69	58	62	54	57	50	64	56	59	52	54	48	52	48	49	45	44	42	38	35			
5.00		71	60	65	56	60	53	66	57	62	54	57	51	55	50	51	47	46	44	40	37			
10.00		76	63	72	61	69	58	71	61	68	59	65	57	60	55	58	53	52	49	46	42			

