



東芝照明器具配光データシート

名 称	H I D埋込ダウンライト
形 名	DD-1048C (S)

保守率	良	0.47
	中	0.44
	否	0.42



光源	名 称	H L-ネオハイドランプ
	形 名	MF100・L-J/B U
	光束	6500 lm × 1

効 率	F	0 %
	F	82 %
	F	82 %
	器具 光束	5350 lm

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備 考	
--------	--

前 面	カバー (透明)
反射面	銀色鏡面仕上げ

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	390		
10°	449		
20°	484		
30°	408		
40°	250		
50°	123		
60°	33		
70°	6		
80°	3		
90°	3		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		59	54	49	46	42	41	58	53	48	46	42	41	47	45	41	40	41	40	37	36
0.80		68	62	58	55	52	50	66	61	57	54	51	49	56	53	50	49	49	48	45	44
1.00		76	68	66	61	60	57	74	67	65	61	59	56	63	60	58	56	57	55	52	51
1.25		81	72	73	66	66	62	79	71	71	66	65	62	69	65	64	61	62	60	58	56
1.50		85	75	77	70	71	66	83	74	76	69	70	66	73	68	68	65	66	64	62	60
2.00		91	79	84	75	78	72	88	78	82	74	77	71	78	73	74	70	72	69	67	65
2.50		94	81	88	78	83	75	91	80	86	77	81	74	82	75	78	73	75	72	70	68
3.00		96	82	91	79	86	77	93	81	88	79	84	76	84	77	81	75	77	74	72	71
4.00		99	84	94	82	91	80	96	83	92	81	88	79	87	79	84	78	80	76	75	73
5.00		100	85	97	83	94	81	97	84	94	82	91	81	88	80	86	79	82	78	76	75
10.00		104	87	102	86	100	85	100	86	98	85	97	84	92	83	91	82	85	81	79	78

