

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42800-P N9

名称	メロウライン
形名	FHF32EX-N-H
光束	3520 lm × 2

前 面	
反射面	塗装 (白)

良	0.73
中	0.69
否	0.61

効 率	F $\frac{1}{2}$	0 %
	F $\frac{1}{4}$	83 %
	F $\bigcirc$	83 %
器具 光束		5870 lm



最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	275	275	275
10°	268	273	273
20°	261	259	262
30°	250	236	245
40°	224	205	221
50°	180	168	186
60°	127	124	134
70°	93	77	83
80°	24	29	29
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80						70						50						30		20	0
	壁	床	70		50		30		70		50		30		50		30		30		10	0		
			30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																						
0.60		52	48	40	38	32	31	50	47	39	37	32	31	38	36	32	31	31	30	27	25			
0.80		62	56	50	47	42	41	60	55	49	46	42	40	47	45	41	40	40	39	35	34			
1.00		68	61	56	52	49	46	66	60	55	52	48	46	53	50	47	45	46	44	41	39			
1.25		75	66	64	58	56	52	72	65	62	58	55	52	60	56	53	51	52	50	46	45			
1.50		79	70	69	62	61	57	76	68	67	61	60	56	64	60	58	55	56	54	51	49			
2.00		86	75	77	69	70	64	83	74	75	68	69	63	71	66	66	62	64	61	58	56			
2.50		90	78	82	73	76	68	87	76	80	72	74	68	76	70	71	66	68	65	62	60			
3.00		93	80	86	75	80	71	90	79	84	74	78	71	79	73	75	70	71	68	65	64			
4.00		97	82	91	79	86	76	93	81	88	78	84	75	83	76	80	74	76	72	70	68			
5.00		99	84	95	81	90	78	96	83	91	80	88	78	86	78	83	76	79	75	73	71			
10.00		104	87	102	86	99	84	100	86	98	85	96	83	92	83	90	82	85	80	78	77			

