



東芝照明器具配光データシート

名 称	電球直付器具
形 名	IG-2995

良	0.79
中	0.74
否	0.70



光 源	名 称	
	形 名	FIRE110V10W T20E12
	光 束	55 lm × 1

効 率	F	0 %
	F	22 %
	F	22 %
	器具 光束	12 lm

最大取付間隔	
A-A	1.1 H
B-B	1.1 H

備 考	
-----	--

前 面	カバー (乳白)
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	73		
10°	55		
20°	55		
30°	55		
40°	55		
50°	36		
60°	36		
70°	36		
80°	18		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		12	11	9	8	7	6	12	11	9	8	7	6	8	8	6	6	6	6	5	5		
0.80		14	13	11	10	9	8	14	13	11	10	9	8	10	10	8	8	8	8	7	6		
1.00		17	15	13	12	11	10	16	14	13	12	11	10	12	11	10	10	10	10	8	8		
1.25		18	16	15	14	13	12	18	16	14	13	12	12	14	13	12	11	11	11	10	9		
1.50		20	17	16	15	14	13	19	17	16	15	14	13	15	14	13	13	13	12	11	11		
2.00		21	19	19	17	16	15	21	18	18	16	16	15	17	16	15	15	15	14	13	13		
2.50		23	20	20	18	18	16	22	19	20	18	18	16	18	17	17	16	16	16	15	14		
3.00		24	20	21	19	20	17	23	20	21	18	19	17	19	18	18	17	17	16	16	15		
4.00		25	21	23	20	21	19	24	21	22	20	21	19	21	19	20	18	19	18	17	16		
5.00		26	22	24	21	23	20	25	21	23	20	22	19	22	20	21	19	20	19	18	17		
10.00		27	23	26	22	25	22	26	22	25	22	25	21	24	21	23	21	22	20	20	19		

