

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42745-P N9

光源	名称	メロウライン
	形名	FHF32EX-N-H
	光束	3520 lm × 2

前 面	
反射面	塗装 (白)

保守率	良	0.73
	中	0.69
	否	0.61

効 率	F 	0 %
	F 	65 %
	F 	65 %
	器具 光束	4612 lm



最大取付間隔	
A-A	1.1 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	312	312	312
10°	301	309	309
20°	281	295	292
30°	217	273	257
40°	118	242	187
50°	57	201	99
60°	31	151	44
70°	17	93	20
80°	7	30	8
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		45	42	37	35	32	31	44	41	36	35	31	31	35	34	31	30	31	30	27	26		
0.80		54	49	45	42	40	38	52	48	45	42	40	38	43	41	39	38	38	37	35	34		
1.00		58	52	50	46	44	42	56	51	49	46	44	42	47	45	43	41	42	41	38	37		
1.25		62	55	55	50	49	46	61	55	54	50	49	46	52	49	47	45	46	45	42	41		
1.50		65	58	58	53	53	49	63	57	57	52	52	49	55	51	51	48	49	48	45	44		
2.00		70	61	64	57	59	54	68	60	63	57	58	54	60	55	56	53	54	52	50	49		
2.50		73	63	68	60	63	57	71	62	66	59	62	56	62	58	59	55	57	55	53	51		
3.00		75	64	70	61	66	59	72	63	68	61	65	58	65	59	62	57	59	57	55	53		
4.00		78	66	74	64	70	62	75	65	71	63	68	61	67	62	65	60	62	59	57	56		
5.00		79	67	76	65	73	63	76	66	73	64	71	63	69	63	67	62	64	60	59	58		
10.00		82	69	80	68	79	67	79	68	78	67	76	66	73	66	71	65	67	64	62	61		

