

東芝照明器具配光データシート



名 称	蛍光灯ロフトペンダント
形 名	SN-43000 (W) -PM

光 源	名称	コンパクト形蛍光ランプ
	形名	FHT42EX-N
	光束	3200 lm × 3

前 面	下面開放
反射面	プリズム (乳白タイプ)

良	0.66
中	0.63
否	0.55

効 率	F 	13 %
	F 	72 %
	F 	85 %
	器具光束	8103 lm



最大取付間隔	
A-A	1.6 H
B-B	1.6 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	193		
10°	201		
20°	208		
30°	218		
40°	213		
50°	166		
60°	100		
70°	52		
80°	27		
90°	18		
100°	19		
110°	21		
120°	22		
130°	22		
140°	22		
150°	21		
160°	17		
170°	11		
180°	7		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		50	46	38	36	31	30	48	44	37	35	30	29	35	33	29	28	27	27	23	21		
0.80		60	55	48	45	41	39	58	53	47	44	40	38	44	42	38	37	36	35	31	29		
1.00		66	60	55	51	47	45	63	58	53	50	46	44	49	47	43	42	41	40	36	33		
1.25		73	65	62	57	54	51	70	63	60	55	53	50	56	52	50	48	47	45	41	39		
1.50		77	68	67	61	59	55	74	66	64	59	58	54	60	56	54	51	51	49	45	42		
2.00		84	73	75	67	68	62	80	71	72	65	66	61	66	62	61	58	57	55	51	48		
2.50		88	76	80	71	74	66	84	73	77	69	71	65	70	65	66	62	61	59	55	52		
3.00		91	78	84	73	78	69	86	76	80	71	75	68	73	68	69	65	64	61	58	54		
4.00		95	80	89	77	84	74	90	78	85	75	80	72	77	71	74	68	68	65	61	58		
5.00		97	82	92	79	87	76	92	79	88	77	84	74	80	73	77	70	70	67	64	60		
10.00		102	85	99	83	96	82	96	83	94	81	91	80	85	77	83	75	76	71	69	65		

