

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42944K-PN9

光源	名 称	メロウライン
	形 名	FHF32EX-N-H
	光 束	3520 lm × 2

前 面	バッフル (黒)
反射面	塗装 (白)

保守率	良	0.69
	中	0.65
	否	0.61

効 率	F 	0 %
	F 	55 %
	F 	55 %
	器具光束	3851 lm



最大取付間隔	
A-A	1.0 H
B-B	1.2 H

備 考

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	269	269	269
10°	254	261	262
20°	227	239	235
30°	182	209	198
40°	120	173	150
50°	76	132	95
60°	53	88	56
70°	30	44	31
80°	11	12	12
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		37	34	30	29	26	25	36	34	30	28	26	25	29	28	25	25	25	24	22	21		
0.80		44	40	37	35	33	31	43	39	37	34	32	31	35	34	32	31	31	30	28	27		
1.00		48	43	41	38	36	34	46	42	40	38	36	34	39	37	35	34	34	33	31	30		
1.25		52	46	45	41	41	38	50	45	44	41	40	38	43	40	39	37	38	37	35	34		
1.50		54	48	48	44	44	41	53	47	47	43	43	40	45	42	42	40	40	39	37	36		
2.00		58	51	53	47	49	45	56	50	52	47	48	44	49	46	46	44	45	43	41	40		
2.50		61	52	56	49	52	47	59	51	54	49	51	47	52	48	49	46	47	45	43	42		
3.00		62	53	58	51	55	49	60	53	57	50	54	48	54	49	51	48	49	47	45	44		
4.00		65	55	61	53	58	51	62	54	59	52	57	51	56	51	54	50	51	49	48	47		
5.00		66	56	63	54	61	53	64	55	61	53	59	52	57	52	56	51	53	50	49	48		
10.00		69	57	67	57	66	56	66	57	65	56	64	55	61	55	60	54	56	53	52	51		

