

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42938K-PN9

光源	名称	メロウライン
	形名	FHF32EX-N-H
	光束	3520 lm × 2

前 面	カバー（プリズム）
反射面	塗装（白）

保守率	良	0.69
	中	0.65
	否	0.61

効 率	F 	0 %
	F 	65 %
	F 	65 %
	器具光束	4576 lm



最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	303	303	303
10°	299	291	300
20°	282	276	284
30°	251	245	253
40°	193	191	202
50°	124	116	119
60°	72	68	49
70°	37	36	24
80°	15	15	16
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		45	41	37	35	31	30	44	41	36	34	31	30	35	34	31	30	30	30	27	26		
0.80		53	48	45	42	40	38	52	47	44	42	39	38	43	41	39	37	38	37	35	34		
1.00		58	52	50	46	44	42	56	51	49	46	44	42	47	45	43	41	42	41	38	37		
1.25		62	55	55	50	49	46	60	54	54	50	49	46	52	49	47	45	46	45	42	41		
1.50		65	57	58	53	53	49	63	56	57	52	52	49	55	51	51	48	49	48	45	44		
2.00		70	61	64	57	59	54	68	60	62	56	58	54	59	55	56	53	54	52	50	49		
2.50		73	63	67	59	63	57	70	62	65	59	62	56	62	57	59	55	57	54	53	51		
3.00		75	64	70	61	66	59	72	63	68	60	64	58	64	59	61	57	59	56	55	53		
4.00		77	65	73	63	70	61	74	65	71	63	68	61	67	61	65	60	62	59	57	56		
5.00		79	66	75	65	72	63	76	66	73	64	70	62	69	63	67	61	63	60	59	57		
10.00		82	68	80	67	78	66	79	67	77	67	76	66	72	65	71	64	67	63	62	61		

