

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42943K-PN9

光源	名 称	メロウライン
	形 名	FHF32EX-N-H
	光 束	3520 lm × 2

前 面	ルーバー
反射面	塗装（白）

保守率	良	0.73
	中	0.69
	否	0.61

効 率	F 	0 %
	F 	72 %
	F 	72 %
	器具光束	5076 lm



最大取付間隔	
A-A	1.2 H
B-B	1.5 H

備考	0A3
----	-----

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	295	295	295
10°	290	291	294
20°	272	308	287
30°	244	326	290
40°	207	292	271
50°	155	200	203
60°	29	29	29
70°	15	17	16
80°	5	6	5
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		50	46	40	38	35	33	48	45	40	38	34	33	39	37	34	33	33	33	30	29
0.80		59	54	50	47	45	43	58	53	50	47	44	42	48	46	43	42	43	42	39	38
1.00		65	58	56	52	50	48	63	57	55	51	50	47	53	50	48	47	47	46	44	42
1.25		70	62	62	57	56	53	68	61	61	56	56	52	59	55	54	52	53	51	49	47
1.50		73	65	66	60	61	56	71	64	65	59	60	56	62	58	58	55	56	54	52	51
2.00		79	69	73	65	68	62	76	68	71	64	66	61	68	63	64	60	62	60	57	56
2.50		82	70	76	67	72	65	79	69	74	67	70	64	71	65	67	63	65	62	60	59
3.00		84	72	79	69	75	67	81	71	77	68	73	66	73	67	70	65	67	64	62	61
4.00		86	73	82	71	79	69	83	72	80	70	77	69	75	69	73	68	70	66	65	63
5.00		88	74	84	72	81	71	85	73	82	72	79	70	77	70	75	69	71	68	66	65
10.00		91	76	89	75	87	74	87	75	86	74	84	73	80	72	79	72	74	70	69	68

