

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-54310-P N9

光 源	名 称	コンパクト形蛍光ランプ
	形 名	FHP45EN
	光 束	4350 lm × 4

前 面	下面開放
反射面	塗装（白）

良	0.73
中	0.69
否	0.61

効 率	F 	0 %
	F 	72 %
	F 	72 %
器具 光束	12515 lm	



最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備 考	
-----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	265	265	265
10°	265	260	263
20°	261	247	256
30°	250	225	241
40°	220	194	216
50°	157	155	175
60°	74	110	106
70°	25	63	36
80°	10	17	11
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井						70						50						30		20	0
	壁						70						50						30		10	0
	床						30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数	照 明 率 (×0.01)																					
0.60	47	43	37	35	31	30	45	42	36	34	30	29	35	34	30	29	29	29	26	25		
0.80	56	51	46	43	40	38	54	50	45	43	39	38	44	42	39	37	38	37	34	33		
1.00	61	55	52	48	45	43	59	54	51	47	45	43	49	46	44	42	43	42	38	37		
1.25	67	59	58	53	51	48	65	58	57	52	51	48	54	51	49	47	48	47	44	42		
1.50	70	62	62	56	56	52	68	61	61	56	55	52	58	54	53	51	52	50	47	46		
2.00	76	66	69	62	63	58	74	65	67	61	62	57	64	60	60	57	58	56	53	52		
2.50	79	68	73	65	68	61	77	67	71	64	67	61	68	62	64	60	61	59	56	55		
3.00	82	70	76	67	72	64	79	69	74	66	70	63	70	64	67	62	64	61	59	58		
4.00	85	72	80	69	76	67	82	71	78	69	74	67	73	67	71	65	67	64	62	61		
5.00	87	73	83	71	79	69	83	72	80	70	77	68	75	69	73	67	69	66	64	63		
10.00	90	75	88	74	86	73	87	75	85	73	83	72	80	72	78	71	74	70	68	67		

