

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-54300-P N9

光源	名 称	蛍光ランプ
	形 名	FHP45EN
	光 束	4350 lm × 4

前 面	下面開放
反射面	塗装 (白)

保守率	良	0.73
	中	0.69
	否	0.61

効 率	F 	0 %
	F 	74 %
	F 	74 %
	器具 光束	12873 lm



最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	248	248	248
10°	247	244	246
20°	244	232	239
30°	237	213	227
40°	218	185	207
50°	171	149	176
60°	113	107	123
70°	49	62	65
80°	13	20	14
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		照 明 率 (×0.01)																						
0.60		46	43	36	34	30	29	45	42	35	34	29	28	34	33	29	28	28	28	24	23			
0.80		56	51	45	43	39	37	54	50	45	42	38	37	43	41	37	36	37	36	32	31			
1.00		61	55	51	47	44	42	59	54	50	47	44	42	48	46	43	41	42	41	37	36			
1.25		67	60	58	53	51	48	65	58	56	52	50	47	54	51	49	47	47	46	43	41			
1.50		71	63	62	56	55	51	69	61	61	56	54	51	58	54	53	50	51	49	46	45			
2.00		77	67	69	62	63	58	75	66	68	61	62	57	64	60	60	56	58	56	53	51			
2.50		81	70	74	65	68	62	78	68	72	64	67	61	68	63	64	60	61	59	56	55			
3.00		83	71	77	68	72	64	80	70	75	67	70	64	71	65	67	63	64	62	59	58			
4.00		87	74	82	71	78	68	83	73	79	70	75	67	75	68	72	66	68	65	63	61			
5.00		89	75	84	72	81	70	85	74	82	72	79	70	77	70	74	68	71	67	65	64			
10.00		93	77	90	76	88	75	89	76	87	75	85	74	82	74	80	73	76	71	70	69			

