

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-54301-P N9

光源	名 称	コンパクト形蛍光ランプ
	形 名	FHP45EN
	光 束	4350 lm × 4

前 面	バッフル (白)
反射面	塗装 (白)

保守率	良	0.73
	中	0.69
	否	0.61

効 率	F 	0 %
	F 	72 %
	F 	72 %
	器具 光束	12456 lm



最大取付間隔	
A-A	1.4 H
B-B	1.2 H

備 考	
-----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	255	255	255
10°	254	249	251
20°	252	232	241
30°	244	206	225
40°	227	172	201
50°	184	132	166
60°	121	87	112
70°	55	46	54
80°	11	16	14
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		45	42	35	34	29	28	44	41	35	33	29	28	34	32	29	28	28	28	25	23		
0.80		55	50	45	42	38	37	53	49	44	41	38	36	42	40	37	36	36	36	32	31		
1.00		60	54	50	47	44	41	58	53	49	46	43	41	47	45	42	41	41	40	37	36		
1.25		66	58	56	52	50	47	63	57	55	51	49	46	53	50	48	46	46	45	42	41		
1.50		69	61	61	55	54	50	67	60	59	54	53	50	57	53	52	49	50	49	46	44		
2.00		75	65	68	61	62	57	73	64	66	60	61	56	63	58	59	55	56	54	52	50		
2.50		78	68	72	64	67	60	76	67	70	63	65	60	66	61	62	59	60	58	55	54		
3.00		81	69	75	66	70	63	78	68	73	65	69	62	69	64	66	61	63	60	58	56		
4.00		84	71	79	69	75	66	81	70	77	68	73	66	73	66	70	64	66	63	61	60		
5.00		86	73	82	70	79	68	83	72	79	70	76	68	75	68	72	66	69	65	63	62		
10.00		90	75	88	74	86	73	86	74	85	73	83	72	79	71	78	71	73	69	68	66		

