

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42800-P D9

光源	名 称	メロウライン
	形 名	FHF32EX-N-H
	光 束	4950 lm × 2

前 面	
反射面	塗装 (白)

保守率	良	0.73
	中	0.69
	否	0.61

効 率	F 	0 %
	F 	80 %
	F 	80 %
	器具 光束	7910 lm



最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備 考	
--------	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	263	263	263
10°	255	261	261
20°	248	248	251
30°	237	226	234
40°	214	197	211
50°	172	161	177
60°	121	120	130
70°	89	75	78
80°	24	28	30
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		49	46	38	36	31	30	48	44	37	36	31	30	36	35	30	29	30	29	26	24		
0.80		59	54	48	45	40	39	58	53	47	44	40	39	45	43	39	38	38	37	34	32		
1.00		65	59	54	50	46	44	63	57	53	49	46	44	51	48	45	43	44	42	39	37		
1.25		72	64	61	56	53	50	69	62	60	55	52	50	57	54	51	49	50	48	44	43		
1.50		76	67	66	60	58	54	73	65	64	59	57	54	61	57	55	53	54	52	48	47		
2.00		82	72	74	66	67	61	80	70	72	65	66	61	68	63	63	60	61	59	55	54		
2.50		86	74	79	69	72	65	83	73	76	69	71	65	72	67	68	63	65	62	59	58		
3.00		89	76	82	72	77	68	86	75	80	71	75	68	76	69	71	66	68	65	63	61		
4.00		93	79	87	76	83	73	90	78	85	75	80	72	80	73	76	71	73	69	67	65		
5.00		95	80	90	78	86	75	92	79	88	77	84	74	82	75	79	73	75	72	69	68		
10.00		100	83	97	82	95	81	96	82	94	81	92	80	88	79	86	78	81	77	75	73		

