

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42939K-PD9

光源	名 称	メロウライン
	形 名	FHF32EX-N-H
	光 束	4950 lm × 2

前 面	カバー (乳白)
反射面	塗装 (白)

保守率	良	0.69
	中	0.65
	否	0.61

効 率	F 	0 %
	F 	54 %
	F 	54 %
	器具光束	5332 lm



最大取付間隔	
A-A	1.2 H
B-B	1.3 H

備 考

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	195	195	195
10°	186	193	193
20°	175	182	182
30°	159	165	164
40°	138	142	142
50°	111	114	114
60°	80	83	83
70°	47	50	49
80°	16	17	17
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80								70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0				
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0				
室指数		照 明 率 (×0.01)																							
0.60		34	31	26	25	22	21	33	30	26	25	21	21	25	24	21	21	21	20	18	17				
0.80		41	37	33	31	28	27	39	36	32	31	28	27	31	30	27	26	27	26	24	23				
1.00		44	40	37	34	32	30	43	39	36	34	32	30	35	33	31	30	30	29	27	26				
1.25		49	43	42	38	37	34	47	42	41	38	36	34	39	37	35	34	34	33	31	30				
1.50		51	45	45	41	40	37	50	44	44	40	39	37	42	39	38	36	37	36	33	32				
2.00		56	49	50	45	46	42	54	48	49	44	45	41	46	43	43	41	41	40	38	37				
2.50		58	50	53	47	49	44	56	49	52	46	48	44	49	45	46	43	44	42	40	39				
3.00		60	52	56	49	52	46	58	51	54	48	51	46	51	47	48	45	46	44	43	41				
4.00		63	53	59	51	56	49	60	52	57	50	54	49	54	49	52	48	49	47	45	44				
5.00		64	54	61	52	58	51	62	53	59	52	57	50	56	51	54	49	51	48	47	46				
10.00		67	56	66	55	64	54	65	55	63	55	62	54	59	53	58	53	55	52	51	50				

