

東芝照明器具配光データシート



名 称	白熱灯器具
形 名	ID-7395SC (W)

光源	名 称	ミニクリプトンランプ
	形 名	KR100/110V5 7W
	光 束	800 lm × 1

前 面	下面開放
反射面	塗装 (白)

保守率	良	0.81
	中	0.77
	否	0.67

効 率	F 	0 %
	F 	60 %
	F 	60 %
	器具 光束	484 lm



最大取付間隔	
A-A	0.8 H
B-B	0.7 H

備 考	
--------	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	411	411	409
10°	344	361	336
20°	275	257	281
30°	221	208	241
40°	162	167	186
50°	106	118	124
60°	46	54	57
70°	15	19	17
80°	9	11	10
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		41	37	33	31	28	27	40	37	32	31	27	27	31	30	27	26	27	26	24	23
0.80		47	43	40	37	34	33	46	42	39	37	34	33	38	36	33	32	33	32	30	29
1.00		53	48	45	42	40	38	52	47	45	42	40	38	43	41	39	38	38	37	35	34
1.25		57	51	50	46	45	42	56	50	49	46	45	42	47	45	43	42	42	41	39	38
1.50		61	53	54	49	49	46	59	52	53	48	48	45	51	47	47	45	45	44	42	41
2.00		65	56	59	53	55	50	63	56	58	52	54	50	55	51	52	49	50	48	46	45
2.50		68	58	63	55	59	53	65	57	61	55	57	52	58	53	55	51	53	51	49	48
3.00		69	59	65	57	61	55	67	59	63	56	60	54	60	55	57	53	55	52	51	50
4.00		72	61	68	59	65	57	69	60	66	58	63	57	62	57	60	56	57	55	53	52
5.00		73	62	70	60	67	59	71	61	68	59	66	58	64	58	62	57	59	56	55	53
10.00		76	64	74	63	73	62	73	63	72	62	70	61	67	61	66	60	62	59	58	57

