



# 東芝照明器具配光データシート

名称	無電極シリーズ高天井用反射笠
形名	HE-16102W-200H

保守率	良	0.74
	中	0.70
	否	0.61



光源	名称	無電極放電ランプ
	形名	QL165W
	光束	12000 lm × 1

効率	F ◡	0%
	F ◣	77%
	F ○	77%
	器具光束	9238 lm

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

備考	反射笠 : SN-10044A
----	-----------------

前面	
反射面	複合膜処理

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	584		
10°	589		
20°	526		
30°	369		
40°	217		
50°	89		
60°	10		
70°	3		
80°	2		
90°	2		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10		
室指数	照明率 (×0.01)																			
0.60	63	58	55	52	50	48	62	57	54	52	49	48	53	51	49	48	48	47	45	44
0.80	72	66	65	61	60	57	71	65	64	60	59	57	62	60	58	57	58	56	54	53
1.00	76	68	69	64	64	61	75	68	68	63	63	60	66	63	62	60	61	59	57	56
1.25	80	71	73	67	68	64	78	71	72	67	68	64	70	66	66	63	65	63	61	60
1.50	83	73	77	70	72	67	81	72	75	69	71	66	73	68	69	66	67	65	63	62
2.00	88	76	82	73	78	71	85	75	80	73	76	70	77	71	74	69	71	69	67	66
2.50	90	77	85	75	81	73	87	77	83	74	79	72	79	73	76	71	73	70	69	68
3.00	91	78	87	76	83	74	89	78	85	76	82	74	81	74	78	73	75	72	70	69
4.00	94	80	90	78	87	76	91	79	88	77	85	76	83	76	81	75	77	73	72	71
5.00	95	80	92	79	89	78	92	79	89	78	87	77	84	77	82	76	78	74	73	72
10.00	98	82	96	81	95	80	94	81	93	80	91	80	87	79	86	78	81	77	75	74

