

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42941NK- -PN9

光 源	名 称	メロウライン
	形 名	FHF32EX-N-H
	光 束	3520 lm × 2

前 面	ルーバー
反射面	塗装（白）

良	0.73
中	0.69
否	0.61

効 率	F 	0 %
	F 	72 %
	F 	72 %
	器具 光束	5077 lm



最大取付間隔	
A-A	1.2 H
B-B	1.7 H

備 考	0A1
-----	-----

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	292	292	292
10°	288	286	290
20°	270	318	292
30°	245	353	306
40°	211	326	302
50°	167	226	237
60°	1	1	1
70°	0	0	0
80°	0	0	0
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		50	46	41	39	36	34	49	46	41	39	35	34	40	38	35	34	34	34	31	30
0.80		61	55	52	49	46	44	59	54	51	48	46	44	50	47	45	44	44	43	40	39
1.00		66	59	57	53	52	49	64	58	56	53	51	49	55	52	50	48	49	48	45	44
1.25		71	63	64	58	58	55	69	62	62	58	57	54	60	57	56	54	55	53	51	49
1.50		75	66	68	61	62	58	73	65	66	61	61	58	64	60	60	57	58	56	54	53
2.00		80	70	74	66	69	63	78	69	72	66	68	63	69	64	66	62	64	61	59	58
2.50		83	71	77	68	73	66	80	70	76	68	72	66	72	66	69	65	66	64	62	61
3.00		85	72	80	70	76	68	82	72	78	69	74	67	74	68	71	66	68	65	64	63
4.00		87	74	83	72	80	70	84	73	81	71	78	70	76	70	74	69	71	67	66	65
5.00		88	75	85	73	82	72	85	74	82	72	80	71	78	71	76	70	72	69	67	66
10.00		91	76	89	75	87	74	88	75	86	74	84	73	80	73	79	72	75	71	69	68

