



東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FHR-41909NK- -PN9

保守率	良	0.69
	中	0.65
	否	0.61



光源	名 称	蛍光ランプ
	形 名	FHF32EX-N-H
	光 束	3520 lm × 1

効 率	F	0 %
	F	43 %
	F	43 %
	器具 光束	1518 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備 考	
--------	--

前 面	乳白アクリルカバー
反射面	塗装（白）

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	163	163	163
10°	159	159	157
20°	150	152	150
30°	134	135	135
40°	115	117	115
50°	92	95	92
60°	64	69	66
70°	35	37	36
80°	7	8	7
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		27	25	21	20	18	17	27	25	21	20	18	17	20	20	17	17	17	17	15	14
0.80		33	30	27	25	23	22	32	29	26	25	23	22	25	24	22	22	22	21	19	19
1.00		36	32	30	28	26	25	35	32	29	28	26	25	28	27	25	24	25	24	22	21
1.25		39	35	34	31	30	28	38	34	33	31	29	28	32	30	29	27	28	27	25	24
1.50		41	36	36	33	32	30	40	36	35	32	32	30	34	32	31	29	30	29	27	26
2.00		45	39	41	36	37	34	43	38	40	36	36	34	38	35	35	33	34	32	31	30
2.50		47	40	43	38	40	36	45	40	42	38	39	36	40	37	37	35	36	34	33	32
3.00		48	41	45	39	42	38	47	41	44	39	41	37	41	38	39	37	38	36	35	34
4.00		50	43	48	41	45	40	49	42	46	41	44	39	43	40	42	39	40	38	37	36
5.00		51	43	49	42	47	41	50	43	48	42	46	41	45	41	43	40	41	39	38	37
10.00		54	45	53	44	51	44	52	44	51	44	50	43	47	43	47	42	44	41	41	40

